

IN THE CLAIMS:

Please amend claims 1-7 as follows:

1. (Currently Amended) A pistol with a hollow pistol grip (2) which receives a magazine (3) for rounds insertable from below, the magazine, when completely inserted, being retained in the pistol grip, characterised in that the magazine (3) has comprising a lug (12; 52) on its front wall, that in the front part of the pistol grip (3), a sliding block (8; 38) is arranged to be displaceable in transverse direction, which sliding block is held in a middle position thereof by at least one spring (9; 10), in which middle position the lug (12; 52) of the magazine (3) rests on the sliding block (8; 38), and that the sliding block (8; 38) has having a respective vertical groove (21; 22; 41; 42) on each side of the lug (12; 52), which groove, by displacement of the sliding block (8; 38) in either one of the two directions, can be brought into the path of movement of the lug (12; 52) when inserting the magazine (3).

2. (Currently Amended) A pistol with a magazine for rounds according to claim 1, ~~characterised in that~~ wherein the sliding block (8; 38) is held in its middle position by two counter-acting bar springs (9; 10) which are approximately vertically mounted in the interior of the pistol grip (2).

3. (Currently Amended) A pistol with a magazine for rounds according to claim 2, ~~characterised in that~~ further including stop faces (11) ~~are provided~~ in the interior of the pistol grip (2) ~~which delimit the path of the bar springs (9, 10).~~

4. (Currently Amended) A pistol with a magazine for rounds according to claim 1, ~~characterised in that~~ wherein one (21) of the two grooves (21, 22) widens downwardly so that, at its lower end, it extends into the path of movement of the lug (12) during insertion of the magazine (3), wherein the lug (12) temporarily moves the sliding block (8) out of its middle position, against the force of at least one spring (9, 10).

5. (Currently Amended) A pistol with a magazine for rounds according to claim 1, ~~characterised in that~~ wherein the lug (12) of the magazine of rounds is attached by notching and bending out.

6. (Currently Amended) A pistol with a magazine for rounds according to claim 1, ~~characterised in that~~ wherein the lug (12) is injection-moulded to the magazine.

7. (Currently Amended) A pistol with a magazine for rounds according to claim 1, ~~characterised in that~~ wherein the lug (52) on the front wall of the magazine (3) of rounds is resiliently elastic and, by its movable lower end (53), is seated on the sliding block.